



Casambi Gateway

Perfect integration of the Casambi Bluetooth system
in lighting control systems



The Casambi Gateway enables Ethernet-based integration of the Casambi Bluetooth system into a cross-system building management or comprehensive lighting control system such as the EUTRAC NetComposer – including a variety of innovative options. Whether bidirectional communication, programming via web interface, coupling two Casambi Bluetooth networks via Ethernet, programming 16 commands (incoming or outgoing), the Casambi Gateway opens up new dimensions in professional lighting control via smartphone and tablet.

Casambi to Ethernet Network

- Scenes called up at Casambi can initiate Ethernet Network commands

Ethernet Network to Casambi

- Call scenes
- Groups can be set to value
- Broadcast level can be called up
- Casambi button can be emulated (on request)
- Transfer of brightness sensor values (on request)
- Transfer of movement values (on request)

Casambi Gateway

558 3 0020 0



EUTRAC

eutrac.de

Customer service Germany

Herderstrasse 18
40721 Hilden, Germany
P: +49 (0)2103/90 85 6-0
F: +49 (0)2103/90 85 6-29
service@eutrac.de

Customer service international

Sperenberger Strasse 1
12277 Berlin, Germany
P: +49 (0)30/27 0009-0
F: +49 (0)30/27 0009-248
export@eutrac.de