



R E C E S S E D



CUT-OUT HOLE: 290 x 55 mm



	PURE VERSION	SMART VERSION	Premium VERSION	VERSION AVAILABLE AT THE END OF 2021
AIR FLOW	126 m³/h	126 m³/h	126 m³/h	
APP DEVICE	✗	iOS & ANDROID	iOS & ANDROID	
IOT 4.0	✗	✓	✓	
SMART CONTROL	✗	CASAMBI 🚩	CASAMBI 🚩	
FILTERS	PREFILTER (DUST CAPTURE) TiO₂ FILTERS + UV-A LED	PREFILTER (DUST CAPTURE) TiO₂ FILTERS + UV-A LED	PREFILTER (DUST CAPTURE) TiO₂ FILTERS + UV-A LED	
NOISE	from 15 dBa to 50 dBa	from 15 dBa to 50 dBa	from 15 dBa to 50 dBa	
RATED VOLTAGE	220 ÷ 240 Vac	220 ÷ 240 Vac	220 ÷ 240 Vac	
POWER CONSUMPTION	38 W	38 W	38 W	
ROOM COVERAGE	UP TO 150 m² *	UP TO 150 m² *	UP TO 150 m² *	
AIR QUALITY SENSOR	✗	TEMPERATURE - HUMIDITY PRESSURE - TVOC CO2 rel. - IAQ - AIR FLOW	TEMPERATURE - HUMIDITY PRESSURE - TVOC CO2 rel.- IAQ - AIR FLOW INFLAMMABLE GAS - PM10	

(*) The flow rate is indicative, as it varies according to the type of environment / ventilation present.
The data shown refers to an open space (ceiling 3m / h) and with forced ventilation (e.g. shops / offices)