Wireless pushbutton with rocker

Manuals and documents in further languages:
http://eltako.com/redirect/F2T55E-

F2T55E-

Wireless 2-way pushbutton in E-Design55, 80x80 mm external dimensions, internal frame dimensions 55x55 mm, 15 mm high. Generates the power for wireless telegrams itself when the button is pressed, therefore there is no connecting wire and no standby loss.

Wireless pushbuttons with one rocker can transmit two evaluable signals: press rocker up and press rocker down.
The mounting plate can be screwed over a flush-mounting box with a screw spacing of 60 mm or screwed on a flat surface. The wireless pushbutton can be glued to the wall, on glass or on furniture using the enclosed adhesive foil.

F2T55E-am*	Wireless 2-way pushbutton in E-Design55, anthracite mat	Art. No. 30055718	**52,30 €/pc.**
F2T55E-pg*	Wireless 2-way pushbutton in E-Design55, polar white glossy	Art. No. 30055702	**52,30 €/pc.**
F2T55E-pm*	Wireless 2-way pushbutton in E-Design55, polar white mat	Art. No. 30055727	**52,30 €/pc.**
F2T55E-wg*	Wireless 2-way pushbutton in E-Design55, pure white glossy	Art. No. 30055715	**52,30 €/pc.**
F2T55EOR-am*	Wireless 2-way pushbutton in E-Design55, anthracite mat	Art. No. 30056718	**49,70 €/pc.**
F2T55EOR-pg*	Wireless 2-way pushbutton in E-Design55, polar white glossy	Art. No. 30056702	**49,70 €/pc.**
F2T55EOR-pm*	Wireless 2-way pushbutton in E-Design55, polar white mat	Art. No. 30056727	**49,70 €/pc.**
F2T55EOR-wg*	Wireless 2-way pushbutton in E-Design55, pure white glossy	Art. No. 30056715	**49,70 €/pc.**

OR types without single frames included in the scope of delivery, for mounting in multiple or third-party frames.

Recommended retail prices excluding VAT.

* The F1T55E buttons can be used in vertically and horizontally mounted multiple frames RxUE55. The multiple frames must be processed accordingly at predetermined breaking points.